

AGRICO Row Crop Cultivator



MODEL RANGE, ROW CROP CULTIVATOR

ROW SPACING	ROWS	WHEELS	TIRE SIZE
0,9 m	4	-	-
	6	2	6.00-16
	8	2	7.50-16
1,5 m	3	-	-
	5	2	7.50-16
2,3 m	2	-	-
	3	2	6.00-16
(0,9 + 2,3) m	2	2	6.00-16
	3	2	7.50-16

THE BEST ROW CROP CULTIVATOR AVAILABLE

- The **AGRICO** cultivator is a high quality implement for the cultivation of row crops at up to 12 km/h built with the best technology and -materials with a model for every configuration.
- Highly suitable for seedbed preparation and ideal for moisture conservation and prevention of wind erosion.
- **Heavy duty** – Famous DVS tines mounted on a robust spring and shank for extreme conditions.
- **Standard duty** – Famous spring steel S-tines with helper springs are adjustable and ensure very low draught requirements, due to high frequency vibrations and very narrow streamlined profile at share fixing point. This result in very low fuel consumption and production costs.
- High frame clearance of 800 mm prevents clogging from weeds and other material.
- An 8-row cultivator for 0,9 m rows will do 7,3 ha/h at 12 km/h - i.e. approx 100 ha on a summer's day.
- Gauge wheels with solid rubber tyres and two sealed for life ball bearings (not needle rollers) ensure accurate depth control of each section to prevent damage to roots.
- All hinge points are fitted with large replaceable fibre bushes for a long service life and ease of maintenance. (Hinge point holes will not become oval and sections remain rigid).
- Low maintenance cost due to low share prices and single bolt fixing of shares.
- Wider models have high flotation gauge wheels to stabilize main beam.
- These wheels are used to transport cultivator sideways. The sideways transport width is less than 2,5 m.
- The main beam is a rectangular hollow profile - not boxed channels. The rounded corners reduce crop damage compared to sharp cornered channel beams.
- Three point: CAT 2, 3, 2 quick hitch and 3 quick hitch.
- Optional equipment:
 - Rolling shields to protect small crops.
 - Non corroding fertilizer bins with ground drive for side dressing.

Agrico Row Crop Cultivator 2011-01.29999902.doc

ENQUIRIES: Jannie Venter 📞 072 376 2149 📞 018 632 7260 📞 018 632 5746 ✉️ jannie.venter@agrico.co.za

SALES AND SERVICE WITH BRANCHES ACROSS THE COUNTRY:

• Bellville	• Bethlehem	• Bloemfontein	• Bothaville	• Caledon	• Ceres	• Cradock
• Estcourt	• George	• Hartswater	• Humansdorp	• Kakamas	• Kimberley	• Kroonstad
• Lichtenburg	• Malmesbury	• Moorreesburg	• Nelspruit	• Nigel	• Nylstroom	• Vredendal
• Pietermaritzburg	• Piketberg	• Rawsonville	• Tzaneen	• Upington	• Ventersdorp	• Vredendal

AGRICO

*Meer as 100 jaar van diens!
More than 100 years' service!*

AGRICO Rygewasskoffel



MODELREEKS, RYGEWASSKOFFEL

RY SPASIEËRING	RYE	WIELE	BANDGROOTTE
0,9 m	4	-	-
	6	2	6.00-16
	8	2	7.50-16
1,5 m	3	-	-
	5	2	7.50-16
2,3 m	2	-	-
	3	2	6.00-16
(0,9 + 2,3) m	2	2	6.00-16
	3	2	7.50-16

DIE BESTE SKOFFEL OP DIE MARK

- Die **AGRICO** skoffel is 'n hoë gehalte implement ontwerp vir die skoffel van rygewasse (tot 12 km/h), vervaardig van die beste materiaal en tegnologie.
- Uiters geskik vir saadbedvoorbereiding en ideaal vir vobgewaring en voorkoming van winderosie.
- **Swaardiens** – Beroemde DVS tande word gebruik op 'n robuuste veer en skag vir ekstreme omstandighede.
- **Standaardiens** - Beroemde veerstaal S-tande toegerus met hulpvere, is verskuifbaar en sorg vir die besonder lae trekkragbenodigdhede a.g.v. smal profiel en hoëfrekwensie vibrasies. Dit lei tot lae brandstof verbruik en produksie koste.
- Hoë grondvryhoogte verhoed onkruidpakprobleme met 'n balkvryhoogte van 800 mm.
- 'n Agt ry skoffel vir 0,9 m rye kan teen 12 km/h maklik 7,3 ha/h bewerk - d.i. ongeveer 100 ha op 'n somersdag.
- Soliede rubber dieptebeheerwiele toegerus met 2 geseëde koeëllaers (nie naaldrollers nie) verseker akkurate dieptebeheer van elke skoffelseksie om wortelbeskadiging te voorkom.
- Skarnierpunte is toegerus met groot vervangbare kunsveselbussies vir 'n lang lewe en maklike instandhouding (skarnierpunte se gate word nie ovaal nie en seksies raak nie lendelam nie).
- Ekonomiese instandhouding a.g.v. baie billike skaarpryse, en omrede skare met een boutjie vasheg.
- Wye modelle is toegerus met hoëflottasie dieptebeheerwiele vir akkurate beheer van hoofbalk.
- Dié wiele word gebruik om die skoffel in die langsrigting te vervoer met wydte van minder as 2,5 m.
- Hoofbalk is van rondhoekige reghoekbuis (nie kanaalstaal nie).
- 'n Model vir elke rywydte.
- Driepunt: KAT 2 en 3 asook 2 snel en 3 snel.
- Opsionele toerusting: Rolskerms vir die beskerming van klein plantjies.
Roeswerende kunsmisbakke volledig met grondaandrywing vir kant aandrywing

Agrico Row Crop Cultivator 2011-01.29999902.doc

NAVRAE: Jannie Venter ☎ 072 376 2149 ☎ 018 632 7260 ☎ 018 632 5746 ✉ jannie.venter@agrico.co.za

VERKOPE EN DIENS MET TAKKE OOR DIE LAND:

- | | | | | | | | |
|--------------------|--------------|----------------|--------------|-------------|---------------|-------------|---|
| • Bellville | • Bethlehem | • Bloemfontein | • Bothaville | • Caledon | • Ceres | • Cradock | • |
| • Estcourt | • George | • Hartswater | • Humansdorp | • Kakamas | • Kimberley | • Kroonstad | • |
| • Lichtenburg | • Malmesbury | • Moorreesburg | • Nelspruit | • Nigel | • Nylstroom | • | • |
| • Pietermaritzburg | • Piketberg | • Rawsonville | • Tzaneen | • Uppington | • Ventersdorp | • Vredendal | • |

AGRICO

*Meer as 100 jaar van diens!
More than 100 years' service!*