

AGRICO T1250 Reset Ripper



MODEL RANGE, T1250				
TINE	WORK WIDTH (m)	EST. POWER (kW)	GAUGE WHEELS	3-POINT
1	0,5	75	Optional	✓
3	1,5	120	Optional	✓
5	2,5	200	Optional	✓
7	3,5	280	Optional	✓

DIESTE RIPPER IN ITS CLASS

- The **AGRICO** T1250 is a proven and popular reset ripper.
- Ideal working depth from 600 to 800 mm.
- Frame clearance 1 250 mm.
- Breakaway force 12 500 N (1 250 kg).
- Power needed per tine is \pm 40 - 75 kW.
- The reset is automatic, without reducing speed or raising the implement.
- The tine spacing is easily adjustable, with a standard spacing of 500 mm.
- Very low draught force.
- The tines are manufactured from Roqlast steel for high strength and long life.
- The tine geometry assures excellent trash flow and resistance to plugging.
- The only implement in its class with rebound shock absorbers.
- Equipped with the proven straight ripper shares.
- The shares are securely bolted to the tines, avoiding inadvertent loss of shares.

AGRICO T1250 Ripper 2011-01.29999906.docx

ENQUIRIES: Jannie Venter 📞 072 376 2149 📠 018 632 7260 📠 018 632 5746 📧 jannie.venter@agrico.co.za

SALES AND SERVICE WITH BRANCHES ACROSS THE COUNTRY:

- | | | | | | | | |
|--------------------|--------------|----------------|--------------|------------|---------------|-------------|---|
| • Bellville | • Bethlehem | • Bloemfontein | • Bothaville | • Caledon | • Ceres | • Cradock | • |
| • Estcourt | • George | • Hartswater | • Humansdorp | • Kakamas | • Kimberley | • Kroonstad | • |
| • Lichtenburg | • Malmesbury | • Moorreesburg | • Nelspruit | • Nigel | • Nylstroom | • | • |
| • Pietermaritzburg | • Piketberg | • Rawsonville | • Tzaneen | • Upington | • Ventersdorp | • Vredendal | • |

AGRICO

*Meer as 100 jaar van diens!
More than 100 years' service!*

AGRICO T1250 Herset Ripper



MODELREEKS, T1250				
TANDE	WERKWYDTE (m)	GESKATTE DRYWING (kW)	DIEPTEWIELE	3-PUNT
1	0,5	75	Opsioneel	✓
3	1,5	120	Opsioneel	✓
5	2,5	200	Opsioneel	✓
7	3,5	280	Opsioneel	✓

DIE BESTE RIPPER IN SY KLAS

- Die **AGRICO** T1250 is 'n getoetsde en gewilde herset ripper.
- Die ideale werkdiepte is van 600 tot 800 mm.
- Balkvryhoogte 1 250 mm.
- Wegbreekkrag is 12 500 N (1 250 kg).
- Drywing benodig per tand is $\pm 40 - 75$ kW.
- Die herset is outomaties, sonder om spoed te verminder of die implement te lig.
- Die tande kan maklik verskuif word, met 'n standaard spasiëring van 500 mm.
- Baie lae trekweerstand.
- Skagte vervaardig van Roqlast staal, vir ekstra sterkte en 'n lang lewensduur.
- Tand geometrie verseker goeie stoppelvloei en weerstand teen verstopping.
- Die enigste implement in sy klas met terugslag skokabsorbeerders, vir langer lewe.
- Toegerus met 'n bekende reguit ripperskaar.
- Die skare bout vas, wat die afval van skare verminder.

AGRICO T1250 Ripper 2011-01.29999906.docx

NAVRAE: Jannie Venter 📞 072 376 2149 📠 018 632 7260 📠 018 632 5746 📧 jannie.venter@agrico.co.za

VERKOPE EN DIENS MET TAKKE OOR DIE LAND:

- Bellville • Bethlehem • Bloemfontein • Bothaville • Caledon • Ceres • Cradock •
- Estcourt • George • Hartswater • Humansdorp • Kakamas • Kimberley • Kroonstad •
- Lichtenburg • Malmesbury • Moorreesburg • Nelspruit • Nigel • Nylstroom •
- Pietermaritzburg • Piketberg • Rawsonville • Tzaneen • Upton • Ventersdorp • Vredendal •

AGRICO

*Meer as 100 jaar van diens!
More than 100 years' service!*