

AGRICO T800 Reset Ripper



MODEL RANGE, T800					
TINES	WORK WIDTH (m)	EST. POWER (kW)	GAUGE WHEELS	3-POINT	DRAWN
3	1,2	48	-	✓	×
5	2,0	80	-	✓	×
7	2,8	112	-	✓	×
9	3,6	144	2-7.50-16	✓	×
11	4,4	176	2-7.50-16	✓	✓
13	5,2	208	2-7.50-16	✓	✓
15	6,0	240	2-7.50-16	✓	✓

THE BEST RIPPER IN ITS CLASS

- The **AGRICO** T800 is a proven and popular reset ripper.
- Ideal working depth from 250 to 400 mm.
- Frame ground clearance 800 mm.
- Breakaway force 5 600 N (560 kg).
- Power needed per tine is \pm 16 kW.
- The reset is automatic, without reducing speed or raising the implement.
- The tine spacing is easily adjustable, with a standard spacing of 400 mm.
- Available in 3-point mounted and drawn models.
- Very low draught force.
- The tines are manufactured from Roqlast steel for high strength and long life.
- The tine geometry assures excellent trash flow and resistance to plugging.
- The only implement in its class with rebound shock absorbers.
- Equipped with the proven straight ripper shares.
- The shares are securely bolted to the tines, avoiding inadvertent loss of shares.

AGRICO T800 Ripper 2011-01_29999904.docx

ENQUIRIES: Jannie Venter 📞 072 376 2149 📠 018 632 7260 📠 018 632 5746 ✉ jannie.venter@agrico.co.za

SALES AND SERVICE WITH BRANCHES ACROSS THE COUNTRY:

- | | | | | | | | |
|--------------------|--------------|----------------|--------------|------------|---------------|-------------|---|
| • Bellville | • Bethlehem | • Bloemfontein | • Bothaville | • Caledon | • Ceres | • Cradock | • |
| • Estcourt | • George | • Hartswater | • Humansdorp | • Kakamas | • Kimberley | • Kroonstad | • |
| • Lichtenburg | • Malmesbury | • Moorreesburg | • Nelspruit | • Nigel | • Nylstroom | • | • |
| • Pietermaritzburg | • Piketberg | • Rawsonville | • Tzaneen | • Upington | • Ventersdorp | • Vredendal | • |

AGRICO

*Meer as 100 jaar van diens!
More than 100 years' service!*

AGRICO T800 Herset Ripper



MODELREEKS, T800

TANDE	WERKWYDTE (m)	GESKATTE DRYWING (kW)	DIEPTEWIELE	3-PUNT	SLEEP
3	1,2	48	-	✓	×
5	2,0	80	-	✓	×
7	2,8	112	-	✓	×
9	3,6	144	2-7.50-16	✓	×
11	4,4	176	2-7.50-16	✓	✓
13	5,2	208	2-7.50-16	✓	✓
15	6,0	240	2-7.50-16	✓	✓

DIE BESTE RIPPER IN SY KLAS

- Die **AGRICO** T800 is 'n getoetsde en gewilde herset ripper.
- Die ideale werksdiepte is van 250 tot 400 mm.
- Raam grondvryhoogte 800 mm.
- Wegbreekkrag is 5 600 N (560 kg).
- Drywing benodig per tand is ± 16 kW.
- Die herset is outomaties, sonder om spoed te verminder of die implement te lig.
- Die tande kan maklik verskuif word, met 'n standaard spasiëring van 400 mm.
- Beskikbaar in 3-punt of sleepmodelle.
- Baie lae trekweerstand.
- Skagte vervaardig van Roqlast staal, vir ekstra sterkte en 'n lang lewensduur.
- Tand geometrie verseker goeie stoppelvloei en weerstand teen verstopping.
- Die enigste implement in sy klas met terugslag skokabsorbeerders, vir langer lewe.
- Toegerus met 'n bekende reguit ripperskaar.
- Die skare bout vas, wat die afval van skare verhinder.

AGRICO T800 Ripper 2011-01.29999904.docx

NAVRAE: Jannie Venter 📞 072 376 2149 📠 018 632 7260 📠 018 632 5746 📧 jannie.venter@agrico.co.za

VERKOPE EN DIENS MET TAKKE OOR DIE LAND:

- | | | | | | | | |
|--------------------|--------------|----------------|--------------|------------|---------------|-------------|---|
| • Bellville | • Bethlehem | • Bloemfontein | • Bothaville | • Caledon | • Ceres | • Cradock | • |
| • Estcourt | • George | • Hartswater | • Humansdorp | • Kakamas | • Kimberley | • Kroonstad | • |
| • Lichtenburg | • Malmesbury | • Moorreesburg | • Nelspruit | • Nigel | • Nylstroom | • | • |
| • Pietermaritzburg | • Piketberg | • Rawsonville | • Tzaneen | • Upington | • Ventersdorp | • Vredendal | • |

AGRICO

*Meer as 100 jaar van diens!
More than 100 years' service!*