


## 268 PC



### 2" Full- & Part-Circle Big Gun Sprinkler

**Primary applications:** Permanent or mechanized irrigation including pivot end-guns and travelers. Sugarcane, horse pastures, padlocks, arenas, feedlots, dust control, sod farms.

- Slow rotation at uniform speed.
- Heavy-duty brass and stainless-steel construction for improved wear life and performance.
- Corrosion resistant stainless-steel spring and shaft.
- Three-nozzle construction wide diameter coverage and excellent water distribution.
- Non-clog straightening vane for wider irrigation range and wind-resistant droplets.
- Body trajectory - 26°

2" Male pipe connection  
Weight: 4.6 kg.

Flow:            23 to 60 m<sup>3</sup>/h    100 to 264 gpm  
Pressure:       4.0 to 8.0 bar     60 to 120 psi  
Max. spacing: 54 m            180 ft.

268 PC			
Nozzle mm	P bar	Q m <sup>3</sup> /h	D m
14.5 x 8.0 x 4.0	5.0	25.1	68
	6.0	27.5	71
	7.0	29.5	75
	8.0	31.7	79
16.0 x 8.5 x 4.0*	5.0	28.8	74
	6.0	31.5	79
	7.0	34.6	84
	8.0	36.2	88
18.0 x 8.5 x 4.0	5.0	34.3	78
	6.0	37.6	84
	7.0	40.6	88
	8.0	43.4	92
20.0 x 8.5 x 4.0	5.0	40.4	80
	6.0	44.3	85
	7.0	47.6	90
	8.0	51.1	95
22.0 x 8.5 x 4.0	5.0	47.2	83
	6.0	51.4	90
	7.0	55.7	95
	8.0	59.6	100

\* Standard nozzle

## 280 PC-SR



### 2" Full- & Part-Circle Slow-Return Big Gun Sprinkler

**Primary applications:** Permanent or mechanized irrigation including pivot end-guns and travelers. Sugarcane, horse pastures, padlocks, arenas, feedlots, dust control, sod farms etc.

- Slow-Return mechanism ensures safe operation.
- Heavy-duty construction for better durability and performance.
- Adjustable diffuser screw allows stream breakage for uniform water distribution.
- Two-nozzle construction for wide-diameter coverage and excellent water distribution.
- Non-clog straightening vane for wider irrigation range and wind-resistant droplets.
- Body trajectory - 17°

2" Female pipe connection  
Weight: 3 kg.

Flow:            13.5 to 39.5 m<sup>3</sup>/h    59 to 173 gpm  
Pressure:       2.0 to 5.0 bar     30 to 70 psi  
Max. spacing: 62 m            203 ft.

280 PC-CR			
Nozzle mm	P bar	Q m <sup>3</sup> /h	D m
12 x 8	3.0	13.4	54
	4.0	15.5	60
14 x 8	3.0	16.8	58
	4.0	19.5	64
	5.0	21.8	68
16 x 8	3.0	20.6	62
	4.0	23.9	68
	5.0	26.7	74
18 x 8	3.0	26.0	66
	4.0	30.3	72
	5.0	33.6	80
20 x 8	3.0	31.2	68
	4.0	36.3	76
	5.0	39.4	86