

233 PC



3/4" Full- & Part-Circle Metal Impact Sprinkler

Primary applications: Where full-circle sprinklers should not over-throw water into restricted areas such as roads, adjoining property and different adjacent crops. All over-head irrigation crops, on hand lines, solid set or mechanically moved systems.

- Heavy-duty all brass construction for durability
- Stainless-steel spring and shaft for corrosion resistance
- Sand and dust protection sleeve for reliable operation and durability
- Plastic non-clog vane (mounted in entrance of nozzle) for wider irrigation range and wind-resistant droplets.
- Body trajectory - 30°

3/4" Female pipe connection
Weight: 570 gr.

Flow: 0.66 to 1.91 m³/h 2.9 to 8.4 gpm
Pressure: 2.0 to 4.5 bar 30 to 65 psi
Max. spacing: 18 m 60 ft.

233 PC			
Nozzle mm	P bar	Q m ³ /h	D m
3.4	2.0	0.66	26
	3.0	0.82	28
	4.0	0.93	30
	4.5	0.98	31
3.9*	2.0	0.87	27
	3.0	1.06	29
	4.0	1.22	31
	4.5	1.28	32
4.4	2.0	1.00	28
	3.0	1.22	30
	4.0	1.38	31
	4.5	1.44	32
4.9	2.0	1.29	30
	3.0	1.58	32
	4.0	1.81	34
	4.5	1.91	35

* Standard nozzle

