


255 PC



1 1/4" Full- & Part-Circle Metal Impact Sprinkler

Primary applications: Wide spacing and center pivots machines. Horse pastures, paddocks, arenas, feedlots, dust control, sod farms.

- Heavy-duty brass and stainless-steel construction for improved durability and performance.
- Corrosion resistant stainless-steel spring and shaft.
- Dual nozzle construction for wide diameter coverage and excellent water distribution.
- Non-clog straightening vane for wider irrigation range and wind-resistant droplets.
- Body trajectory - 28°

1 1/4" Male pipe connection
Weight: 2.8 kg.

Flow:	6.2 to 28 m ³ /h	27 to 123 gpm
Pressure:	4.0 to 7.0 bar	60 to 100 psi
Max. spacing:	48 m	155 ft.

255 PC			
Nozzle mm	P bar	Q m ³ /h	D m
9.0 x 3.2	4.0	6.2	50
	5.0	7.0	52
	6.0	7.8	54
	7.0	8.5	56
10.0 x 3.2	4.0	7.7	52
	5.0	8.6	54
	6.0	9.5	56
	7.0	10.3	58
11.0 x 3.2*	4.0	9.4	54
	5.0	10.6	56
	6.0	11.7	58
	7.0	12.6	60
13.0 x 6.3	4.0	14.3	58
	5.0	16.2	62
	6.0	18.2	68
	7.0	19.5	72
16.0 x 6.3	4.0	20.2	62
	5.0	23.2	66
	6.0	25.8	72
	7.0	28.0	74

* Standard nozzle

