


water application solutions FOR CENTER PIVOT IRRIGATION



Nelson 3000 Series Pivot Products

- | | | | | | |
|-------|-------|-------|-------|-------|-------|
| R | S | N | D | A | T |
| R3000 | S3000 | N3000 | D3000 | A3000 | T3000 |



save water, save energy and do a better job of irrigating.

FROM PIVOT POINT TO END GUN

Nelson Irrigation Corporation offers a full-range of water application solutions for center pivot irrigation. From control valves, to pivot sprinklers and pressure regulators to end guns — the package is complete. Efficiency and effectiveness are at the heart of this superior center pivot irrigation package. **Save water, save energy and do a better job of irrigating with Nelson products.**

PRESSURE REGULATORS

Nelson Pressure Regulators are precision manufactured and feature a patented dampening system, improved plug resistance with a patented single strut design, and extended flow range.



CONTROL VALVES

You'll fully appreciate the extra built-in quality and reliability of a Nelson control valve when it performs under the most demanding operating conditions. Specify a Nelson 800 Series Control Valve at the Pivot Point and as part of your End Gun Control Package.

3000 SERIES PIVOT SPRINKLERS

Only Nelson offers such a complete line of advanced design pivot sprinklers. A highly-intuitive modular system of components make up Nelson's 3000 Series Pivot Products.

BIG GUN[®] SPRINKLERS

All end guns are not the same. Only the Nelson SR series Big Guns[®] have stood the test of time on center pivots — recognized the world over as the leader in quality and performance.



A WORLDWIDE REPUTATION FOR EXCELLENCE

UNIFORMITY BEGINS WITH THE ASSURANCE OF QUALITY.

Nelson Irrigation has the highest standards in engineering design, precision manufacturing, and quality assurance with state-of-the-art sprinkler package design software.

FOCUS ON SOLUTIONS.

Nelson Irrigation offers a complete line of pivot sprinklers that provide the perfect combination of features to irrigate a multitude of crops — corn, cotton, potatoes, alfalfa — to name a few.

CHOOSE HIGH PERFORMANCE.

Nelson's 3000 Series Pivot Products take into account the variety of soils and their differing content of sand, silt, and clay. Water droplet size and energy affect both wind-fighting ability and the integrity of the soil structure. Choose the product that best fits your soil type and maximizes efficiency.

INCREASE PRODUCTIVITY.

Center pivot irrigation has proven itself to be a highly effective and efficient means of irrigation. Take advantage of the benefits of improved uniformity and high application efficiency. Solve problems like runoff, while increasing yield and grade.

MAXIMIZE IRRIGATION EFFICIENCY.

The need to save water, save energy, and do a better job of irrigating is no longer an option — it's a necessity. Nelson Irrigation is focused and very dedicated to doing things that improve the state-of-the-art of agricultural irrigation by making products that maximize efficiency and uniformity at lower pressure.

IT'S SIMPLE

Choose the right sprinkler configuration for your crop type, soil type, system type, and water and energy needs.



SPECIFY NELSON ON BOARD



PRODUCTS THAT MEET YOUR NEEDS

> an irrigation SYSTEM — it's greater than the sum of its parts

S 3000 spinner

GENTLE RAIN AT LOW PRESSURE. The free-spinning action of the S3000 Spinner provides a gentle, rain-like droplet for sensitive soils and crops.

SUPERIOR UNIFORMITY AT LOW PRESSURE. A low pressure alternative to fixed sprayheads, the S3000 provides higher uniformity with better overlap and lower application rates.



R 3000 rotator®

GREATER THROW RADIUS. As a rotating type sprinkler the R3000 Rotator® produces a wider pattern resulting in a lower application rate, reduced runoff and longer soak time.

HIGHER UNIFORMITY. The R3000 greatly improves uniformity because of the increased overlap from adjacent sprinklers.

REDUCED WIND DRIFT AND EVAPORATIVE LOSS. The R3000 more than meets the challenge of putting a rotating type sprinkler on drop tubes — down out of the wind — to minimize wind drift and evaporative loss.



> 3TN



THE 3TN NOZZLE
IS THE CENTER
OF THE 3000
SERIES PIVOT
PRODUCT LINE

A 3000 accelerator

DESIGNED FOR IN-CANOPY WATER APPLICATION. A hybrid sprinkler using both Rotator® and Spinner technology, the Accelerator increases rotation speed as the nozzle size increases. This maximizes throw distance and minimizes evaporative losses at low flow rates. At the end of the system it transforms into a Spinner to lower instantaneous application rates while treating the soil correctly.

MAXIMUM APPLICATION EFFICIENCY. Operating at 10 psi (.7 BAR) the A3000 maintains the lowest possible trajectory angle without sacrificing throw distance.



N 3000 nutator®

DESIRED DROPLETS AT LOW PRESSURE. The N3000 Nutator® is designed for operation at 10-15 psi (.7-1.0 BAR). Choose from two plate designs to best fit specific irrigation needs.

HIGH UNIFORMITY. Designed for optimal performance from the pivot point to the end of the machine, the N3000 Nutator provides uniformity through the nozzle range.

WIND-FIGHTING DROPLET. By maintaining the lowest possible trajectory angle without sacrificing throw distance, the N3000 Nutator provides unsurpassed wind-fighting ability for maximum application efficiency.



NOZZLE

EXPANDED
NOZZLE RANGE

QUICK-CHANGE

COLOR-CODED

COMMON TO
ALL 3000 SERIES
SPRINKLERS

HIGH WEAR-
RESISTANCE

PRECISION
ACCURACY



D 3000 sprayhead

GERMINATE, IRRIGATE & CHEMIGATE. The flip-over dual spray cap allows easy conversion of the spray pattern. Choose from spray plate options to germinate, irrigate, and chemigate.

“LOW ENERGY DOWN IN THE CROP”. The sleek, crop-guarded body design provides durability for dragging the D3000 Sprayhead down in tall growing crops like corn.

OPTIONAL LEPA ACCESSORIES. The hose drag adapter allows simple conversion of the D3000 to a hose drag system while the bubbler clip transforms the D3000 into a LEPA “bubbler” device.









T 3000 trashbuster

FLOW CONTROL NOZZLE. The 3000FC Nozzle not only eliminates the need for pressure regulators, but also passes debris more easily. It is not to be used on flexible hose drop assemblies.












BODY DESIGNED FOR WASTEWATER. The open architecture design of the body allows for debris to pass through more easily, alleviating build up of material on the plate and body.

By operating on drop tubes you can distribute effluent more days of the year, keep corrosive water off the pivot structure, eliminate excess wind/pathogen drift, and reduce odor. The T3000 Trashbuster can be configured into either a spray or rotator sprinkler.

> 3000 series		DESCRIPTION	NOZZLE TYPE	OPERATING RANGE	APPLICATION RATE
R R3000	 rotator®	The R3000 Rotator® features the greatest throw distance available on drop tubes. The wide water pattern from rotating streams equates to lower average application rates, longer soak time and reduced runoff. More overlap from adjacent sprinklers improves uniformity.	3TN	15-50 PSI (1-3.4 BAR)	LOW
S S3000	 spinner	The S3000 Spinner utilizes a free-spinning action to produce a gentle, rain-like water pattern. Designed for more sensitive crops and soils, low instantaneous application rates and reduced droplet kinetic energy help maintain proper soil structure.	3TN	10-20 PSI (.7-1.4 BAR)	LOW - MEDIUM
N N3000	 nutator®	The N3000 Nutator® combines a spinning action with a continuously offset plate axis for a highly uniform pattern even in the wind. Larger, wind-penetrating droplets and low trajectory angles reduce wind exposure for maximum application efficiency.	3TN	10-15 PSI (.7-1 BAR)	LOW - MEDIUM
D D3000	 sprayhead	The D3000 Sprayhead is a fixed spray designed with future needs in mind. As irrigation requirements change throughout the season, the D3000 features a flip-over cap to change spray patterns. The D3000 is easily convertible to LEPA or other 3000 Series sprinklers.	3TN	6-40 PSI (.41-2.8 BAR)	HIGH
A A3000	 accelerator	The A3000 Accelerator maximizes performance of in-canopy water application. Designed as a hybrid of Rotator and Spinner technology, the Accelerator increases rotation speed through the nozzle range.	3TN	10-15 PSI (.7-1 BAR)	MEDIUM
T T3000	 trashbuster	Developed for the land application of wastewater, the T3000 Trashbuster features an open-architecture body design to pass debris more easily. Available with the 3000 FC, a plug-resistant, flow compensating sprinkler package can simplify maintenance.	3TN or 3000 FC	Depends on sprinkler selection	LOW - HIGH

*Careful selection of pressure and sprinkler configuration must be taken into account to optimize droplet size.

**Throw Distance Varies with Pressure, Nozzle Size, Mounting Height and Hydraulic Conditions.

MOUNTING	RELATIVE THROW DIAMETER**	FEATURES & BENEFITS
<p>Up Top or On Drops</p>	<p>50-74' (15.2-22.6M)</p> 	<p>MODULARITY = ECONOMY & EFFICIENCY</p> <p>Nelson 3000 Series Pivot Products are easy to change/inter-change to give you the best configuration for your ever-changing conditions.</p>
<p>On Drops</p>	<p>42-54' (12.8-16.5M)</p> 	 <p>A square thread fitting or a square thread Universal Regulator are a great way to connect sprinkler & hose</p>
<p>On Drops (flex hose)</p> <p><small>IMPORTANT! To properly install the N3000 Nutator and maintain warranty, it is necessary to mount with a minimum of 12" (30 cm) of reinforced flexible drop hose. Do not use slip over weights that are secured by the hose clamp.</small></p>	<p>44-52' (13.4-15.9M)</p> 	<p>3TN NOZZLES</p> <ul style="list-style-type: none"> ▪ Quick-Change ▪ Color-Coded ▪ Easily Identifiable
<p>Up Top or On Drops</p>	<p>16-40' (4.9-12.2M)</p> 	 <p>(Odd-numbered nozzles have a color marking the color of the next size nozzle.)</p>  <p>All 3000 Series Pivot Products Bodies have a "CROP-GUARDED" design to prevent hang-ups when the sprinkler is down in the crop.</p>
<p>On Drops</p>	<p>30-46' (9.1-14.0M)</p> 	 <p>The 3000 Series high-performance plates are engineered to provide the optimal droplet size for various conditions.</p>
<p>Up Top or On Drops</p> <p><small>IMPORTANT! Do not use 3000FC with hose drops.</small></p>	<p>Depends on sprinkler selection</p> 	

< 3000 series PIVOT PRODUCTS > modularity is key



3/4" F x 3/4" F			3/4" F x Square Thread		
	Uni-Flo	Hi-Flo		Uni-Flo	Hi-Flo
6 PSI	9491-001	9071-001	6 PSI	9572-001	9611-001
10 PSI	9491-002	9071-002	10 PSI	9572-002	9611-002
15 PSI	9491-003	9071-003	15 PSI	9572-003	9611-003
20 PSI	9491-004	9071-005	20 PSI	9572-004	9611-005
25 PSI	9491-005	9071-006	25 PSI	9572-005	9611-006
30 PSI	9491-006	9071-007	30 PSI	9572-006	9611-007
40 PSI	9491-007	9071-008	40 PSI	9572-007	9611-008
50 PSI	9491-008	9071-009	50 PSI	9572-008	9611-009

This diagram reflects the modularity of Nelson's 3000 Series Pivot Products. Each sprinkler is made up of an assembly of a cap, plate, body, and nozzle. The 3TN Nozzle is interchangeable with all 3000 Series sprinklers. A variety of connection devices are available to link the sprinkler with a hose or rigid drop.



1 lb. Modular
Pivot Weight #10130
Fits on regulator or directly on body
(except the N3000 Nutator)



Universal 3000
Pressure Regulator

R3000 Rotator®/
S3000 Spinner Body #9412



A3000 Accelerator/
D3000 Sprayhead Body #9428



Rotator® R3000

Spinner S3000

A3000 Accelerator

Rotator® Plates



Spinner Plates



Accelerator Plate



Rotator® Cap
(Blue) #9539

PC-R3000
#10843-xxx



PC-S3000
#9926-001



Spinner Cap
(Gray) #9540



Accelerator Cap
(Maroon) #10402



3TN Nozzle #9461-xxx



3000FC Nozzle #10106-xxxx



flow control nozzle requires rigid drop

N3000 Nutator®/
T3000 Trashbuster Body #10419



D3000 Sprayhead

Spray Plates



Flip-Over Spray Cap (Black) #9429

Spray Plate with Cap Assembly #10041-xxxx

PC-D3000 #9894-001



N3000 Nutator®

Nutator® Plates *With Cap Only



Nutator® Cap Assembly (Green) *#10319-001



Nutator® Cap Assembly (Blue) *#10319-002

T3000 Trashbuster

Rotator® Plates



Rotator® Cap (Blue) #9539

Spray Plates



Trashbuster Cap (Purple) #10133

Spray Plate with Cap Assembly #10324-xxx

> UNIVERSAL FLO 3000 series PRESSURE REGULATORS

The function of a pressure regulator in center pivot sprinkler design is to fix a varying inlet pressure to a set outlet pressure, regardless of changes in the system pressure due to hydraulic conditions, elevation changes, pumping scenarios, etc. The benefits include a uniform depth of water application, controlled sprinkler performance (droplet size and throw distance), and flexibility in system operation. Specify Nelson's Universal Flo 3000 Series Regulator in your sprinkler package.

WIDE FLOW RANGE

The Nelson Universal Pressure Regulator has a flow up to 12 GPM (2.7 M³/H) at 15 PSI (1.0 BAR) and above.

PATENTED DAMPENING SYSTEM

A patented o-ring dampening system handles severe pressure surges to withstand water hammer.



PATENTED PLUG RESISTANT DESIGN

Improved plug-resistance with a new single-strut seat design in both the Hi-Flo and Universal Flo models.

EXTENDED PERFORMANCE & PRECISION ACCURACY

Precision components coupled with an internally lubricated o-ring minimize frictional drag and hysteresis.

CHEMICALLY RESISTANT MATERIALS

UNIVERSAL 3000 SERIES CONNECTION

Integral adapter connects directly into all Nelson 3000 Series Sprinklers.



1 LB. WEIGHT FOR FLEXIBLE HOSE DROPS

The modular weight fits onto all Nelson Pressure Regulators. When pressure regulators are not used, the weight fits securely on the body of 3000 Series sprinklers (not to be fitted directly on the N3000 Nutator). The 1 lb. Modular Pivot Weight is designed for Nelson 3000 Series products operating at 20 PSI (1.4 BAR) and below.

TECHNICAL TIPS FOR REGULATING SYSTEMS

IMPORTANT: Allow approximately 5 PSI (.35 BAR) extra pressure in order for the regulator to function properly. For example, the minimum design pressure for a 20 PSI (1.4 BAR) pressure regulator is 25 PSI (1.7 BAR).

IMPORTANT: If your system is designed with Nelson sprinklers, use Nelson Pressure Regulators. Individual manufacturers' pressure regulator performance varies. Interchanging could result in inaccurate nozzle selection.

> 3000 series PIVOT ACCESSORIES

3TN DUAL & TRIPLE NOZZLE CLIPS

SAVE WATER WITH SMART TOOLS.

Nelson 3000 Series sprinklers can be equipped with two or three nozzles using the 3TN Dual Nozzle Clip or 3TN Triple Nozzle Clip. These allow you to precisely match crop water requirements through the season. During germination, lower system flow rates lessen the intensity of water droplets to maintain proper soil structure and reduce runoff. Adjust the system flow as crop water requirements change.

- Change system flow quickly and accurately.
- No more fumbling with or dropping nozzles.
- Meet differing in-season demands:
 - Germinate at LO, Irrigate at HI
 - Irrigate at HI, Chemigate at LO

NOTE: Do not operate in down-in-the-crop applications, or with the D3000 Chemigation Plate.




NEW! 3TN TRIPLE NOZZLE CLIP



LEPA APPLICATIONS

D3000 SPRAYHEAD WITH BUBBLER CLIP

Transform the D3000 Sprayhead into a LEPA Bubbler by inverting the D3000 Cap and attaching a bubbler clip to the D3000 Body. (Not to be used with second spray plate.)



HD3000 HOSE DRAG ADAPTER

For (LEPA) low energy precision application, utilize the 3/4" hose drag adapter on the 3000 Series to apply a hose drag or a drag sock. With LEPA, the plant canopy remains dry and water is applied directly to the furrow — typically every other furrow. Pressure regulators are generally a necessity for good LEPA uniformity of nozzle discharge.

Solve Wheel Track Problems with Part-Circle Sprinklers

PROBLEM:

Excessive water in the wheel tracks can cause slippage of the tires, causing the system to slow down in wet areas and steep slopes — increasing the application depth in relation to other parts of the fields. Deep wheel track ruts are also detrimental to the equipment and harvesting efficiency.

SOLUTION:

Nelson part circle sprinklers direct the water off of the pivot structure at the towers and away from the wheel track to prevent deep wheel track ruts. Overall field uniformity can be maintained by preventing excessive slippage of the tires, and maintaining a uniform speed of travel.



HOSE BARB FITTINGS

USER-FRIENDLY. Easy installation of hose barb into 3/4" flexible hose.

EASY THREAD INSTALLATION. The convenience of the 15/16" Hex Adapter is unique to Nelson fittings. Secure fittings using 15/16" deep well socket or open end wrench.

ELIMINATE ADDITIONAL FITTINGS.



3/4" FNPT



3/4" MNPT



3000 ST
(#9901 — square thread for 3000 Series)

SAVE WATER, SAVE ENERGY
AND DO A BETTER JOB OF IRRIGATING WITH NELSON 3000 SERIES PIVOT PRODUCTS.



> IMPACT and BIG GUN SPRINKLERS

P85AS
20 GPM-125 GPM
(4.5 M³/H-28.4 M³/H)



SR75
30 GPM-160 GPM
(6.8 M³/H-36.3 M³/H)



SRN100
50 GPM-300 GPM
(11.4 M³/H-68.2 M³/H)



SR100
50 GPM-300 GPM
(11.4 M³/H-68.2 M³/H)

BIG GUN SPRINKLERS. In the field of large-volume sprinklers, Nelson Big Guns® are recognized the world over as the leader in quality and performance. They are engineered and precision manufactured for heavy-duty reliability and long wear life with minimum maintenance required. Every Nelson Big Gun® is subjected to the toughest inspection testing and quality control standards in the industry. The SR (Slow Reverse) series of Big Guns® is far and away the number one choice for center pivot end gun use around the world.

With its proven dual arm drive and patented dual drive spoon, the SR gun reverses at the same slow, steady speed as it drives forward. This greatly reduces the vibration and whipping action of the old fast reverse system, which puts excessive stress and strain on the carrying device.

PLASTIC IMPACT SPRINKLER PACKAGES

F44AAB



8° Low Angle

Save Inventory & Cost – The F44AAB requires only one model of sprinkler to cover from pivot point to end gun.

Save Water & Energy – The 8° low angle body minimizes wind exposure and operates at low pressure for optimum efficiency.

Heavy Duty – Featuring a Seal-Lock™ Bearing design, wear life is extended in tough field conditions. Engineering grade plastic provides durability. Select standard or Nelson FCN® flow control nozzles.

BRASS IMPACT SPRINKLER PACKAGES

F33AA



15° Low Angle

Wide Coverage & Overlap - 15° trajectory maximizes throw distance, while keeping the water pattern down out of the wind.

Extended Wear Life – Precision manufactured from the highest quality materials available. Features the Seal-Lock™ Bearing design for extended wear life in tough field conditions.

Select standard or Nelson FCN® flow control nozzles.



Nelson Irrigation Corporation

848 Airport Rd., Walla Walla, WA 99362 USA

Tel: 509.525.7660 Fax: 509.525.7907 info@nelsonirrigation.com

Nelson Irrigation Corporation of Australia Pty. Ltd.

35 Sudbury Street, Darra QLD 4074 info@nelsonirrigation.com.au

Tel: +61 7 3715 8555 Fax: +61 7 3715 8666

WWW.NELSONIRRIGATION.COM

WARRANTY AND DISCLAIMER: Nelson Irrigation Products and Accessories are warranted for one year from date of original sale to be free of defective materials and workmanship when used within the working specifications for which the products were designed and under normal use and service. The manufacturer assumes no responsibility for installation, removal or unauthorized repair of defective parts. The manufacturer's liability under this warranty is limited solely to replacement or repair of defective parts and the manufacturer will not be liable for any crop or other consequential damages resulting from defects or breach of warranty. THIS WARRANTY IS EXPRESSLY IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING THE WARRANTIES OF MERCHANTABILITY AND FITNESS FOR PARTICULAR PURPOSES AND OF ALL OTHER OBLIGATIONS OR LIABILITIES OF MANUFACTURER. No agent, employee or representative of the manufacturer has authority to waive, alter or add to the provisions of this warranty, nor to make any representations or warranty not contained herein.

These products may be covered by one or more of the following U.S. Patent Nos. 3744720, 3559887, 4796811, 4809910, RE33823, DES312865, 5415348, 5409168, 5439174, 5588595, 5671774, 6688539, 7025287, 7140595 and other U.S. Patents pending or corresponding issued or pending foreign patents.



Nelson Irrigation Corporation's worldwide network of professional dealers provides customized water application solutions.